


29400 Series



Designation	Principal Dimensions(mm)				Basic Load Ratings(KN)		Limited Speed(rpm)	Weight (kg)
	d	D	B	rs min	Dynamic(Cr)	Static(Cor)	Oil	
29412	60	130	42	1.5	283	805	2600	2.78
29413	65	140	45	2	330	945	2400	3.44
29414	70	150	48	2	365	1040	2200	4.19
29415	75	160	51	2	415	1190	2100	5.07
29416	80	170	54	2.1	460	1380	1900	6.09
29417	85	180	58	2.1	490	1480	1800	7.2
29418	90	190	60	2.1	545	1680	1700	8.38
29420	100	210	67	3	685	2130	1500	11.5
29422	110	230	73	3	845	2620	1400	15
29424	120	250	78	4	975	3050	1300	18.6
29426	130	270	85	4	1080	3550	1200	23.7
29428	140	280	85	4	1110	3750	1200	25.2
29430	150	300	90	4	1280	4350	1100	30.5
29432	160	320	95	5	1500	5150	1000	37
29434	170	340	103	5	1660	5750	940	45
29436	180	360	109	5	1840	6200	890	52.9
29438	190	380	115	5	2010	6800	840	62
29440	200	400	122	5	2230	7650	790	73.3