


Tapered Roller Bearings with a Ceramic Coating



Designation	Mass	Dimensions						Load Rating		Fatigue Limit Load	Limiting Speed	
		m	d	D	T/2B	r1,2	r3,4	d1	dyn.	stat.	Cur	nG
		kg	mm	mm		min	min	≈	Cr KN	Cor KN	KN	min
F-803477.TR1-J20B	2,64	89,945	146,975	40	3,6	1,5	119	232	355	50	4800	
F-804565.30220-A-J20B	3,7	100	180	37	3	2,5	135	231	290	32	4300	
F-803478.TR1-J20B	9,4	117,475	212,725	63,5	8,1	3,3	162,2	490	720	93	3000	
F-803889.32224-A-J20B	9,15	120	215	61,5	3	2,5	175,2	445	650	84	3000	
F-809028.TR1-J20B	10,2	130	225	67	4	3	174,6	480	710	94	2800	
F-804550.01.TR2S-J20B 1)	6,8	140	190	99	2	1,5	150,1	365	780	74	3400	
Z-577634.01.TR2S-J20B 1)	13,5	140	210	130	2,5	2	175,8	585	1180	75	2800	
Z-580065.30228-A-J20B	8,6	140	250	45,75	4	3	187	390	520	60	2600	
K36990-36920-J20B	3,18	177,81	227,012	30,162	1,5	1,5	203,81	186	400	30	2600	
F-809055.TR1-J20AA 2)	9,34	198,298	282,575	46,038	3,6	3,3	249	345	750	87	2200	
Z-566566.TR1-J20AA	9,28	199,949	282,575	46,038	3,6	3,3	249	345	750	87	2200	
F-807411.TR1-J20B	8,23	240	320	42	3	3	278	380	670	73	2000	
F-809146.TR1-J20AA	18,6	240	336,55	65,088	6,4	3,3	284	640	1250	137	1800	
F-808428.TR1-J20AA	17,2	240,51	336,55	65,088	6,4	3,3	284	640	1250	137	1800	
F-808428.TR1-J20B	17,2	240,5	336,55	65,088	6,4	3,3	284	640	1250	137	1800	
Z-547733.TR1-J20AA	22,3	254	358,775	71,438	3,3	1,5	302,81	720	1370	148	1700	
Z-547733.02.TR1-J20AA	22,3	254	358,775	71,438	3,3	1,5	302,8	720	1370	148	1700	