

Electrically Insulated Spherical Roller Bearings



Part Number							Principal dimensions [mm]		Basic load ratings [kN]		Speed ratings [rpm]		Weight [kg]	ISO 335 Dimensions (ABMA)		Abutment and fillet dimensions [mm]										Value							
NO.	SKF	SKF	SKF	FAG	FAG	FAG	d1	D	B	dyt (Cr)	stc (Cor)	Pu		Speed Ratings	Speed Limiting	d	B	r	1,2 (min)	r3,4 (min)	a da (max)	db (min)	Da (min)	Da (max)	Db (min)	Ca (min)	Ch (min)	ra (max)	rb (max)	e	Y	Yo	
22215CA	22215CAVL0241	22215CAVL2071	22215CAVA3091	22215CAJ20A	22215CAJ20AA	22215CAJ20B	22215CAJ20C	75	130	31	166.90	221.50	2400	3200	1.80																		
22215CC	22215CCVL0241	22215CCVL2071	22215CCVA3091	22215CCJ20A	22215CCJ20AA	22215CCJ20B	22215CCJ20C	75	130	31	166.90	221.50	3000	3800	1.69																		
23032CC	23032CCVL0241	23032CCVL2071	23032CCVA3091	23032CCJ20A	23032CCJ20AA	23032CCJ20B	23032CCJ20C	160	240	60	890	508	1300	1700	9.43																		
23040CA	23040CAVL0241	23040CAVL2071	23040CAVA3091	23040CAJ20A	23040CAJ20AA	23040CAJ20B	23040CAJ20C	200	310	82	890	1650	900	1100	23.39																		
23040CC	23040CCVL0241	23040CCVL2071	23040CCVA3091	23040CCJ20A	23040CCJ20AA	23040CCJ20B	23040CCJ20C	200	310	82	916	1690	1000	1300	22.70																		
23044CA	23044CAVL0241	23044CAVL2071	23044CAVA3091	23044CAJ20A	23044CAJ20AA	23044CAJ20B	23044CAJ20C	220	340	90	116	190	1100	1500	30.30																		
23044CC	23044CCVL0241	23044CCVL2071	23044CCVA3091	23044CCJ20A	23044CCJ20AA	23044CCJ20B	23044CCJ20C	220	340	90	1090	2040	950	1200	29.70																		